

## ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C . ). The first artifact folder for an artifact type receives the letter A, the second B, etc.. Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

08904439BA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

CD(s) containing:

computer program listing

Artifact Type Code: P

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

Artifact Type Code: S

content unspecified or combined

Doc Code: Artifact

Artifact Type Code: U

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact      Artifact Type Code: C

Microfilm(s)

Doc Code: Artifact      Artifact Type Code: F

Video tape(s)

Doc Code: Artifact      Artifact Type Code: V

Model(s)

Doc Code: Artifact      Artifact Type Code: M

Bound Document(s)

Doc Code: Artifact      Artifact Type Code: B

Confidential Information Disclosure Statement or Other Documents  
marked Proprietary, Trade Secrets, Subject to Protective Order,  
Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact      Artifact Type Code X

Other, description: \_\_\_\_\_

Doc Code: Artifact      Artifact Type Code: Z

•

The  
United  
States  
of  
America



The Commissioner of Patents  
and Trademarks

*Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.*

*Therefore, this*

United States Patent

*Grants to the person or persons having title to this patent the right to exclude others from making, using or selling the invention throughout the United States of America for the term of seventeen years from the date of this patent, subject to the payment of maintenance fees as provided by law.*

*Jeffrey M. Sarnoff*

Acting Commissioner of Patents and Trademarks

*Melvinia Gary*  
Attest

# United States Patent [19]

Yock et al.

[11] Patent Number: 4,887,606

[45] Date of Patent: Dec. 19, 1989

## [54] APPARATUS FOR USE IN CANNULATION OF BLOOD VESSELS

[76] Inventors: Paul G. Yock, 25 Cerritos Ave., San Francisco, Calif. 94127; Alan R. Selfridge, 2592 Middlefield Rd., Palo Alto, Calif. 94301

[21] Appl. No.: 296,272

[22] Filed: Jan. 11, 1989

### Related U.S. Application Data

[63] Continuation of Ser. No. 908,556, Sep. 18, 1986, abandoned.

[51] Int. Cl.<sup>4</sup> ..... A61B 8/12

[52] U.S. Cl. ..... 128/662.05; 128/662.06

[58] Field of Search ..... 128/662.05, 662.06

### References Cited

#### U.S. PATENT DOCUMENTS

3,430,625	3/1969	McLeod	.....	128/663
3,556,079	1/1971	Omizo	.....	128/661
3,938,502	2/1976	Bom	.....	128/660
4,249,539	2/1981	Vilkomerson et al.	.....	128/660
4,349,032	9/1982	Koyata	.....	128/660
4,407,294	10/1983	Vilkomerson	.....	128/660
4,428,379	1/1984	Robbins et al.	.....	128/660
4,431,006	2/1984	Trimmer et al.	.....	128/660
4,546,771	10/1985	Eggleton et al.	.....	128/660
4,576,177	3/1986	Webster, Jr.	.....	128/660
4,582,067	4/1986	Silverstein et al.	.....	128/663
4,665,925	5/1987	Millar	.....	128/663

### OTHER PUBLICATIONS

Hisonaga, K. et al, "A New Trans-Digestive Tract Scanner with a Gastro-Fiber-Scope", Proc. 23rd AIUM 1978, p. 108.

*Attorney's Medicolegal Dictionary*, (Schmidts) Bender Publ. Co., N.Y., ©1980, pp. S-167, S-227, T-128.

Primary Examiner—Francis Jaworski  
Attorney, Agent, or Firm—Flehr, Hohbach, Test,  
Albritton & Herbert

[57]

### ABSTRACT

Apparatus for use in cannulation of blood vessels includes a hollow needle having a sharpened end for penetrating tissue, a trocar including a transducer mounted on one end for positioning within the hollow needle for transmitting and receiving ultrasonic waves through the sharpened end of the needle. The trocar further includes a support rod for the transducer and ultrasound damping material attaching the transducer to the support rod. Electrical conductors are provided through the support rod or on the surface of the support rod in contact with electrodes on the front and back surfaces of the transducer for transmitting electrical signals to and from the transducer. A syringe portion is detachably attached from the needle for receiving the back flow of blood when the needle is inserted into a blood vessel.

6 Claims, 2 Drawing Sheets

